RE	. v.	DESCRIPTION	NC	DATE	DI	RAWN	CHECKED	APVD.	
Α				2022-01-0	7 黄	润培	黄润培	孙传松	
В		设计性优化,版本是	升级	2023-05-1	9 黄	润培	孙斌	孙斌	
									CIDCUIT DIACDAM
									<u>CIRCUIT DIAGRAM</u>
0.775		1.50		0.20±0.1 1.50±0.07		X B 0.4	3±0.04 0.50		Switch Connector
4 200 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7									
	1.10 0.95 0.95	1.15 2.30 NO soldering	area 2	0.70			\$55 SC 1:150	2) A	(3D VIEW) 16.0 12.4 DETAL:A
Recommended PAD Layout $\Phi \pm 0.05$ Recommended solder thickness $T=0.10\pm0.01$									
1. RATING:DC 12V, 20mA Max 2. OPERATING FORCE:160±40gf 3. TRAVEL:0.15±0.05mm 4. LIFE:200,000cycles 5. PACKAGE:4500Pcs/Reel									
8	_	BUTTOM	1	LCP	BLACK		_		
7		PLATED	· ·	PHOSPHOR BRONZE	Ag-Plate				<u>いましつがひたがくつ</u>
6		SHELL		PHOSPHOR BRONZE	Ag-Plate		-CN	$oldsymbol{JC}^{\circ}$	谊嘉电子科技有限公司 CNJC ELECTRONICS CO., LTD
5	\rightarrow	COVER	1	LCP	BLACK		TOLERANCES	UNLESS	CLASS:
4	-	FILM	1 7	PI	YELLOW Ag - Plate		OTHERWISE S		☐ CONFIDENTIAL ☐ SECRET ■ GENERAL NAME:
2		CONTACT	3	SUS PHOSPHOR BRONZE	Ag-Plate Ag-Plate		OVER: 1.5mm	±0.2mm	TACT SWTICH

1

ITEM

TERMINAL

HOUSING

PART NAME

2

1

Q'TY

PHOSPHOR BRONZE

LCP

MATERIAL

Ag-Plate

BLACK

FINISH

APPD:

孙传松 22-01-07

CHKD: 黄润培 22-01-07 DR: 黄润培 22-01-07 PART NO.

TS2040-AAFQ-S2W16A

 UNIT
 SCALE
 SHEET
 UNIT

 mm
 1:1
 1/1
 B