




安装孔尺寸

标注: ①-⑦ 尺寸的重点检验尺寸

Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.

1.5 A max. @ 250 VAC.

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC

100mA for both silver.

INSULATION RESISTANCE: 1000 MΩ min.

DIELECTRIC STRENGTH: 1000 VAC min.

OPERATING TEMPERATURE: -25°C to +85°C.

Materials

CASE: PPA (UL 94V-0)

CAP: PA66

HOUSING: Stainless Steel.

ACTUATOR: Alloy, nickel plated.

BUSHING: Alloy, nickel plated.

CONTACT/TERMINALS: Copper alloy silver plated.

RoHS

手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
103	ON	OFF	ON
SCHEMATIC		OPEN	



				公差 TOLERANCES	. X ± 0.4	. XX ± 0.25	角度 ± 5°	UNIT 单位 mm	SCALE 1:1	
				版本 VERSION	A0	比例尺 SCALE	NONE	日期 DATE	2021.9.23	TITLE 图名 Sub-Miniature Toggle Switch
				核准	FEI. LONG. HE	核对	JIE. HAI. LAI	绘图	PENG. GAO	DWG NO. 料号
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY		CHECKED BY		DRAWN BY		PART NO. 型号 XB-ST-0-103-002-RS