



- 1.Outlook:
No burr, no hurt.
- 2.Electronic performance:
 - a:Insulation resistance:
Above DC500V/100MQ;
 - b:Endure voltage:
AC500V at 1 minute;
 - c>Contact resistance:
Under 30mΩ;
- 3.Insertion force & withdrawal force:
0.3~3kgf.
- 4.Salt spray test:24H.
- 5.Meet RoHS.
- 6.Remark * is important specification.

- 1、外观：铜管端面无刮伤、凹点、露铜、无电镀不良；绝缘胶饱满、无拔锋。
- 2、电气性能：a. 绝缘阻抗测试：DC500V，100M Ω 无异状；b. 耐电压测试：AC500V，漏电电流0.5mA，1分钟无异状；
- 3、盐雾试验：正常试验条件能过48小时，盐水浓度5%。

3	绝缘体	111-005	PBT+15%GF	黑色	UL 94V-0
2	中心针	32-160167-01-N	黄铜C3604	镀镍2-3UM	1
1	铜管	61-800145-01-N	黄铜C3604	镀镍2-3UM	1

单位 Unit	mm	一般公差 The general tolerance	7				核准 APPROVED BY	校对 CHECKED BY	制图 DRAWN BY	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	
比例 Scale	5:1	xx.:±0.3	6								
视图 Third angle projection		x.x.:±0.1	5								
		.xx.:±0.05	4								
			3		H65	Ni 1~3um	贺龙飞	赖海杰	龙柳婷	规格 DESCRIPTION:	DC PLUG
			2		C3602	Ni 1~3um				品名 P/N:	XB-DC-8016
			1	PLASTIC	PBT	BLACK				图号 DRAWN NO:	
			NO.	PART	MATERIAL	PLATING					